

TRI-PACKED ADJUSTABLE STREAMLINE CLOSER

Closer - Closers shall be TA model number DC70, full rack and pinion type with cast aluminum body. All closers shall be provided with non-critical hex-key adjustment to independently regulate the sweep, latch and back check. Closers shall be non-handed with full cover and projection of 2-1/2" from the surface of the door. Closer shall have full spring adjustment from size 2 to size 6. The closer shall be pre-adjusted at the factory to size 3 for DC70. Each closer shall be adjusted for each door condition and mounted to allow the maximum degree of swing.

FEATURES

- Aluminum Alloy Body
- Tri-Pack with regular, parallel and top-jamb mounting, instructions and full size template
- Standard spring adjustment from size 2 to 6
- Non handed
- Standard with adjustable sweep, latch and back check
- Full plastic cover
- SRT - Self Reaming and Tapping Screws
- Standard hole pattern and mounting location
- 5 year mechanical warranty
- Finishes - AL, DU



OPTIONS

- DA - Delay Closing Action
- HO - Friction Hold-Open Non-Handed Arm CUSH
- Heavy Duty Parallel Mount Cush Arm HO-CUSH
- Heavy Duty Parallel, Hold-Open Cush Arm
- 70-09 - Drop Plate, Pull-side Mount
- 70-11 - Back Plate - Top Jamb Mount Plate.

CERTIFICATIONS



- ANSI/BMHA A156.4 , Grade 1 certified
- UL /cUL listed R13255
- UL10C listed for positive pressure fire test

DESCRIPTION	SIZE
A. Length of Closer Body	11 3/4"
B. Horizontal Mounting Holes	11 1/8"

Conforms to Standards UL10C and UBC7-2-1997

